

AiM pressure sensor 0-150 PSI

AiM 0-150 PSI pressure sensor is suitable for oil and fuel pressure reading, being able to read pressures up to 150 PSI.

The sensor **part number** is:



- 0-150 PSI 1/8 NPT **X05PSA00150P18K**




Technical characteristics

Supply	8-16 V
Accuracy	< +/- 0.5% FS (CLNH – combined non-linearity and hysteresis)
Characterisation	500 mV/ 0 PSI 4500 mV/ 150 PSI
Consumption	< 10 mA
Temperature working range	from -20°C to 135°C
Sealing	IP66
Housing	316 stainless steel
Weight	30 g
Cable length	400 mm
Thread	1/8 NPT


Drawings and pinouts



Binder connector – Sensor side



Binder connector – Harness side



Pin

- 1
- 2
- 3
- 4

Function

- Analog signal
- GND
- +Vb
- Not connected

Cable color

- White
- Black
- Red

Extension cables

For this sensor connector, standard length extension cables are available, whose part number changes according to their length and to the product the sensor is to be connected to.

Extension cable for connection to:

- MXG/MXG 1.2/MXG 1.2 Strada
- MXS/MXS 1.2/MXS Strada/MXS 1.2 Strada
- MXP/MXP Strada
- MXL2
- MXm
- EVO5
- MXL Strada/Pista/Pro05

Part numbers:

- V02PCB05B** - cable length: 500mm
- V02PCB10B** - cable length: 1000mm
- V02PCB15B** - cable length: 1500mm
- V02PCB20B** - cable length: 2000mm
- V02PCB25B** - cable length: 2500mm
- V02PCB30B** - cable length: 3000mm



Extension cable for connection to:

- Channel Expansion
- EVO4
- EVO4S

Part numbers:

- V02PCB05BTXG** - cable length: 500mm
- V02PCB10BTXG** - cable length: 1000mm
- V02PCB15BTXG** - cable length: 1500mm
- V02PCB20BTXG** - cable length: 2000mm
- V02PCB25BTXG** - cable length: 2500mm
- V02PCB30BTXG** - cable length: 3000mm

